

Tekneka 136D is a temperature and humidity data logger which records up to 16,000 temperature and 16,000 humidity readings with a user-programmable sample rate. It comes with a USB interface for easy setup and data download. Selectable data sampling rates of 2s, 5s, 10s, 30s, 1m, 5m, 10m, 30m, 1hr, 2hr, 3hr, 6hr, 12hr, and 24hr. User-programmable alarm thresholds for temperature and humidity. LCDs current temperature and humidity readings plus Min/Max and alarm status. Place or mount the data logger in the monitoring location (storage bin, truck, cargo hold, freezer, temperature-controlled room, etc.). Connect the data logger to your PC via USB to retrieve readings. It displays the current temperature and humidity plus Min/Max and alarm status so it can be viewed anytime during the recording process.

### Features

- Selectable data sampling rate: 1 second to 24 hours
- LCD displays current readings: Min/Max and Alarm status
- User-programmable alarm thresholds for temperature and humidity
- USB interface for easy setup and data download
- 3.6V Lithium battery for long battery life
- Mounting bracket with combination lock
- Includes Windows® 2000, XP, and 7 compatible analysis software



### Applications

Monitoring and documentation in the industries like Cold Chain, Food Storage, Pharma Storage, Production, Hospitals, Facility Management, and Cargo Hold.

| SPECIFICATION                | RANGE  | ACCURACY  | RESOLUTION |
|------------------------------|--|---|------------|
| <b>Relative Humidity</b>     | : 0 to 100%RH (overall)  | ±5.0% (0 to 20%RH and 80 to 100%RH)<br>±3.5% (20 to 40%RH and 60 to 80%RH)<br>±3.0% (40 to 60%RH)                         | 0.1%RH     |
| <b>Temperature</b>           | : -40 to 70°C (overall)<br><br>: -40 to 158°F                      | ±2°C (-40 to -10°C and 40 to 70°C)<br>±1°C (-10 to 40°C)<br>±3.6°F (-40 to 14°F and 104 to 158°F)<br>±1.8°F (14 to 104°F) | 0.1°C/°F   |
| <b>Memory</b>                | : 32,000 Readings (Relative Humidity: 16,000; Temperature: 16,000) |   |            |
| <b>Data Logging Interval</b> | : 1 second to 24 hours   |   |            |
| <b>Dimension</b>             | : 3.7 x 1.9 x 1.3 inch (94 x 48 x 33mm)                            |   |            |
| <b>Weight</b>                | : 115g   |   |            |

### Ordering Info.

- 136D.....Temperature and Humidity Data Logger
- 14250.....3.6V Lithium Battery

### Packing Includes

- 136D with Mounting Bracket and Combination Lock
- 3.6V Lithium Battery with USB Cable
- Windows® 2000/XP/Vista/7 Compatible Analysis Software

