

# PRESSURE GAUGE

PCE-PG 25



- » **Pressure range: -0.088 ... +2.5 MPa**
- » **Interface: RS485**
- » **Pressure connection: M20 x 1.5 plug**
- » **Operating temperature: -10 ... 50°C / 14 ... 122°F**
- » **10 pressure units**

Our digital pressure gauge is a precise and reliable solution for measuring gas and liquid pressures in industry, laboratories and technology. With a measuring range of -0.088 MPa ... +2.5 MPa and a high resolution of 0.0001 MPa, our digital pressure gauge is ideal for applications that require maximum measuring accuracy. The accuracy is 0.1% FS, which guarantees stable and repeatable measurement results.

Our digital pressure gauge works with a diffused silicon pressure sensor and offers intelligent calibration and linearity correction functions. The zero point is set quickly and precisely within two seconds using a magnetic pen. This ensures consistently high measuring accuracy and reliability. The response time is just 0.5 seconds, allowing rapid pressure changes to be reliably recorded. The device is equipped with a 3.1 inch LCD display, which is easy to read and has a backlight.

The wetted parts are made of stainless steel, making our digital pressure gauge suitable for air, water and non-aggressive oils. The connection is made via an M20 × 1.5 thread. Overload protection up to 1.2 times the maximum pressure range reliably protects the sensor from short-term pressure peaks. With a housing diameter of 112 mm and a weight of just 601 g, the device is space-saving and easy to install.

## Specification

<b>Pressure</b>	
Measurement range up to	-0,088 ... +2,5 MPa
Resolution	0,0001 MPa
Accuracy	0.1 % FS.
<b>Pressure</b>	
Measurement range up to	-0,88 ... +25 bar
Resolution	0,001 bar
Accuracy	0.1 % FS.
<b>Pressure</b>	
Measurement range up to	-12,8 ... +362,6 psi
Resolution	0,1 psi
Accuracy	0.1 % FS.
<b>Pressure</b>	
Measurement range up to	-88 ... +2500 kPa
Resolution	0,1 kPa
Accuracy	0.1 % FS.
<b>Pressure</b>	
Measurement range up to	-0,9 ... +25,49 kgf/cm <sup>2</sup>
Resolution	0,01 kgf/cm <sup>2</sup>
Accuracy	0.1 % FS.
<b>Pressure</b>	
Measurement range up to	-88000 ... +2500000 Pa
Resolution	1 Pa
Accuracy	0.1 % FS.
<b>Pressure</b>	
Measurement range up to	-26 ... +738,3 inHg
Resolution	0,1 inHg
Accuracy	0.1 % FS.
<b>Pressure</b>	
Measurement range up to	-660 ... +18752 mmHg
Resolution	1 mmHg
Accuracy	0.1 % FS.
<b>Pressure</b>	
Measurement range up to	-353 ... +10047 inH <sub>2</sub> O
Resolution	1 inH <sub>2</sub> O
Accuracy	0.1 % FS.
<b>Pressure</b>	
Measurement range up to	-89737 ... +2549350 mmH <sub>2</sub> O

<b>General technical data</b>	
Outputs	4 ... 20 mA
Units	bar, psi, kPa, MPa, kgf/cm <sup>2</sup> , Pa, inHg, mmHg, inH <sub>2</sub> O, mmH <sub>2</sub> O
Connections	M20 x 1.5 mm
Display type	LCD
Display size	3,1 Inch
Interface	RS485
Response time	0,5 s
Measured medium	Water, Oil, Air
Housing	Stainless steel
Overload protection	1.2 times overload
Sensors	Silicon pressure sensor
Protection class (device)	IP56
Power supply	100 ... 240V AC   50/60 Hz
Connector type	Euro plug
(Rechargeable) battery	1 x 3,6 V internal , Lithium-ion battery
Capacity	2600 mAh
Operating conditions	-10 ... 50 °C , 0 ... 95 % RH
Storage conditions	-20 ... 70 °C , 0 ... 85 % RH
Dimensions ( L x W x H )	165 x 112 x 47 mm
Weight	601 g

Resolution	1 mmH <sub>2</sub> O
Accuracy	0.1 % FS.